

Socket - EO-AB/UT/LED/15 - 0804155

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Socket, Pin connector pattern type AB 15A, Screw connection, for USA and other countries, with LED display, gray, for mounting on a DIN rail in the service interface or direct mounting, 125 V AC, 15 A, -60 °C, 105 °C, UL 508



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 5 pc |
| GTIN |  4 055626 226781 |
| GTIN | 4055626226781 |
| Weight per Piece (excluding packing) | 84.000 g |
| Custom tariff number | 85366990 |
| Country of origin | Poland |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 45 mm |
| Height | 75 mm |
| Depth | 57.5 mm |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -60 °C ... 105 °C (Maximum short-term operating temperature 130°C.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |

General

| | |
|-----------------------|------------------|
| Nominal voltage U_N | 125 V AC (60 Hz) |
| Nominal current I_N | 15 A |

Socket - EO-AB/UT/LED/15 - 0804155

Technical data

General

| | |
|--|--------|
| Status display | Yes |
| Contact material | CuZn37 |
| Color | gray |
| Insulating material | PA |
| Flammability rating according to UL 94 | V0 |
| Standards/regulations | UL 508 |
| Country ID | USA |

Connection data

| | |
|---------------------------------------|---------------------|
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 4 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 12 |
| Connection method | Screw connection |

Standards and Regulations

| | |
|--|--------|
| Standards/regulations | UL 508 |
| Flammability rating according to UL 94 | V0 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| | Hexahydromethylphthalic anhydride 25550-51-0 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27142305 |
| eCl@ss 11.0 | 27142305 |
| eCl@ss 4.0 | 27142300 |
| eCl@ss 4.1 | 27142300 |
| eCl@ss 5.0 | 27142300 |
| eCl@ss 5.1 | 27142300 |
| eCl@ss 6.0 | 27142300 |
| eCl@ss 7.0 | 27142305 |

Socket - EO-AB/UT/LED/15 - 0804155

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 8.0 | 27142305 |
| eCl@ss 9.0 | 27142305 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001663 |
| ETIM 6.0 | EC001663 |
| ETIM 7.0 | EC001663 |

Approvals


Approvals

Approvals

UL Listed / cUL Listed / EAC-RoHS / EAC / cULus Listed


Ex Approvals

Approval details

| | | | |
|--------------------|---|---|---------|
| UL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E238705 |
| Nominal voltage UN | 125 V | | |
| Nominal current IN | 15 A | | |

| | | |
|------------|---|---|
| cUL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm |
|------------|---|---|

| | | |
|----------|---|--------------------------|
| EAC-RoHS |  | RU D- DE.HB49.B.00025 |
|----------|---|--------------------------|

| | | |
|-----|---|--------------------------|
| EAC |  | RU C- DE.BL08.B.00511 |
|-----|---|--------------------------|

Socket - EO-AB/UT/LED/15 - 0804155

Approvals

cULus Listed



Accessories

Accessories

Terminal marking

Marker for terminal blocks - UC-TMF 8 - 0818137



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

Marker for terminal blocks - UC-TMF 16 - 0819262



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into flat marker groove, for terminal block width: 16 mm, lettering field size: 15.45 x 5.1 mm, Number of individual labels: 32

Zack Marker strip, flat - ZBF 8:UNBEDRUCKT - 0808781



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into flat marker groove, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

Zack Marker strip, flat - ZBF 16:UNPRINTED - 0827464



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into flat marker groove, for terminal block width: 16 mm, lettering field size: 16.25 x 10.5 mm, Number of individual labels: 50

