Product data sheet Characteristics

GS2AH420

External rotary handle, TeSys GS, red handle, front mounting, 2 positions I-O, NEMA 4-4X, for GS 30A Compact UL





Main

TeSys	
TeSys	
GS2AH	
Rotary handle	
TeSys GS GS1D fuse-switch disconnector	
External frontal	
Red	
Yellow	 -
	TeSys GS2AH Rotary handle TeSys GS GS1D fuse-switch disconnector External frontal Red

Complementary

Marking	O-I	
Rotary handle padlocking	With	
[In] rated current	30 A	
Standards	CSA UL	
Net weight	0.2 Kg	

Environment

NEMA degree of protection	NEMA 4/4X

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	222 G	
Package 1 Height	6.2 Cm	
Package 1 width	17.1 Cm	
Package 1 Length	10.6 Cm	
Package 2 Weight	221 G	
Package 3 Weight	869 G	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised

