## Product data sheet Characteristics

# **GS2AH440**

External rotary handle, TeSys GS, red handle, front mounting, 2 positions I-O, NEMA 4-4X, for GS 30-400A UL





#### Main

Range of product	TeSys	
Range	TeSys	
Device short name	GS2AH	
Product or component type	Rotary handle	
Range compatibility	TeSys GS GS2EU TeSys GS GS2GU TeSys GS GS2JU TeSys GS GS2MU TeSys GS GS2QU	
Type of operating handle	External frontal	-
Handle colour	Red	
Handle front plate colour	Yellow	

#### Complementary

Complementary		
Marking	O-I	
Rotary handle padlocking	With	
[In] rated current	30 A	
	60 A	
	100 A	
	200 A	
	400 A	
Standards	CSA	
	UL	
Net weight	0.24 Kg	

#### Environment

NEMA degree of protection	NEMA 4/4X

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	250 G	
Package 1 Height	6 Cm	
Package 1 width	14 Cm	
Package 1 Length	17 Cm	
Package 2 Weight	5.502 Kg	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interneted as a substitute for and is not to be used for determining suitability or reliability of these products by especific user applications. It is the douty of any sub user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or substitiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <sup>™</sup> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised