

## Commercial status

End-of-Sale Notice :

 End-of-Sale Notice

## Main

Range of product	TeSys
Device short name	GS2AM
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Contacts type and composition	1 NO
Contact operation	Early-break
[I <sub>th</sub> ] conventional free air thermal current	16 A (at 40 °C)
[I <sub>e</sub> ] rated operational current	3 A at 240 V AC-15 6 A at 120 V AC-15 1.5 A at 480 V AC-15 1.8 A at 400 V AC-15 2.8 A at 24 V DC-13 0.15 A at 400 V DC-13 0.27 A at 250 V DC-13 0.55 A at 125 V DC-13 1.4 A at 48 V DC-13

## Complementary

Mechanical durability	5000000 Cycles
Electrical durability	1000000 Cycles AC-15
Product compatibility	GS2
[I <sub>n</sub> ] rated current	1250 A 50 A 200 A 125 A 160 A 400 A 600 A 63 A 800 A 100 A 250 A 32 A 60 A 315 A 630 A
Type of operating handle	External left side External right side External frontal
Net weight	0.015 Kg

## Packing Units

Package 1 Weight	13.608 G
------------------	----------

Product Life Status : **End of commercialisation**

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.