# Product data sheet Characteristics

# GS2GU3N

TeSys GS, disconnect switch, fuse, 3 P, 600 V, UL 60 A, Type J fuse

Product availability: Stock - Normally stocked in distribution facility

Price\*: 336.00 USD



#### Main

IVIAIII		
Range	TeSys	
Product name	TeSys GS	
Device short name	GS2GU	
Product or component type	Switch-disconnector-fuse	
Device application	Protection	
Poles description	3P	
Protected poles description	3t	
Contacts type and composition	3 NO	
[Ith] conventional free air thermal current	60 A 104 °F (40 °C)	
[le] rated operational current	60 A	
Fuse type	UL	
Fuse size	J	
Network type	DC AC	
Network frequency	50/60 Hz	

#### Complementary

Type of operating handle	External frontal	
Mounting support	Plate	
[Ui] rated insulation voltage	750 V	
[Uimp] rated impulse withstand voltage	8 kV	
Rated operational power in W	30 kW 400 V 40 kW 500 V 55 kW 690 V	
Short-circuit withstand	17.6 kA	· · · · · · · · · · · · · · · · · · ·
Mechanical durability	10000 cycles	
Electrical durability	6000 cycles	
Connections - terminals	Power circuit lugs-ring terminals 0.010.02 in² (616 mm²)	
Tightening torque	Power circuit 30.98 lbf.in (3.5 N.m)	i

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

#### Environment

Standards	CSA C22.2 No 4 UL98
IP degree of protection	IP20 IEC 60529 with terminal cover)
Ambient air temperature for operation	-4158 °F (-2070 °C)
Ambient air temperature for storage	-40176 °F (-4080 °C)
Fire resistance	1760 °F (960 °C) body
Maximum Height	5.35 in (136 mm)
Maximum Width	5.88 in (149.3 mm)
Maximum Depth	4.84 in (123 mm)

## Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	l11
GTIN	00785901547143
Package weight(Lbs)	3.8 lb(US) (1.72 kg)
Returnability	Yes
Country of origin	FR

# Packing Units

Package 2 Weight	21.56 lb(US) (9.78 kg)
Package 3 Weight	107.38 lb(US) (48.708 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

#### Contractual warranty

Warranty	18 months