



Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2JU
Product or component type	Switch-disconnector-fuse
Device application	Protection
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I _{th}] conventional free air thermal current	100 A (at 40 °C)
[I _e] rated operational current	100 A
Fuse type	UL
Fuse size	J
Network type	AC DC
Network frequency	50/60 Hz

Complementary

Type of operating handle	External frontal
Mounting support	Plate
[U _i] rated insulation voltage	750 V
[U _{imp}] rated impulse withstand voltage	8 KV
Rated operational power in W	51 KW at 400 V 63 KW at 500 V 90 KW at 690 V
Short-circuit withstand	22 KA
Mechanical durability	10000 Cycles
Electrical durability	6000 Cycles
Connections - terminals	Lugs-ring terminals Power circuit: bars34...42 mm ²
Tightening torque	Power circuit: 4 N.m

Environment

Standards	CSA C22.2 No 4 UL98
IP degree of protection	IP20 conforming to IEC 60529 (with terminal cover)
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-40...80 °C
Fire resistance	960 °C body

Height	186 Mm
Width	149.3 Mm
Depth	122.2 Mm
Net weight	2.761 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.306 Kg
Package 1 Height	15 Cm
Package 1 width	23.5 Cm
Package 1 Length	24.5 Cm
Package 2 Weight	10.036 Kg
Package 3 Weight	50.404 Kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Product Life Status : **Commercialised**