



Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2MU
Product or component type	Switch-disconnector-fuse
Device application	Protection
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I _{th}] conventional free air thermal current	200 A (at 40 °C)
[I _e] rated operational current	200 A
Fuse type	UL
Fuse size	J
Network type	DC AC
Network frequency	50/60 Hz

Complementary

Type of operating handle	External frontal
Mounting support	Plate
[U _i] rated insulation voltage	750 V
[U _{imp}] rated impulse withstand voltage	8 KV
Rated operational power in W	100 KW at 400 V 140 KW at 500 V 185 KW at 690 V
[I _{cm}] rated short-circuit making capacity	2 KA at 400 V
Breaking capacity	1600 A at 400 V
Short-circuit withstand	32 KA
Mechanical durability	10000 Cycles
Electrical durability	6000 Cycles
Connections - terminals	Power circuit: lugs-ring terminals 16...152 mm ²
Tightening torque	Power circuit: 8.5 N.m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	UL98 CSA C22.2 No 4
IP degree of protection	IP20 conforming to IEC 60529 (with terminal cover)
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-40...80 °C
Fire resistance	960 °C body
Height	195 Mm
Width	196.2 Mm
Depth	130 Mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.53 Kg
Package 1 Height	14.5 Cm
Package 1 width	24.5 Cm
Package 1 Length	32 Cm
Package 2 Weight	11.584 Kg
Package 3 Weight	55.868 Kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Product Life Status : **Commercialised**