# Product data sheet Characteristics

## LK4AD10N

TeSys GS - auxiliary contact 100...400A - 1 NO - 1 NC



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 22.05 USD



#### Main

Range	TeSys	:
Product or component type	Auxiliary contact	
Device application	Connection	
Contacts type and composition	1 NO + 1 NC	

#### Complementary

Range compatibility	TeSys GS switch
Contact operation	Early-break
[Ith] conventional free air thermal current	16 A 104 °F (40 °C)
[le] rated operational current	100 A 200 A 400 A
Mechanical durability	5000000 Cycles
Type of operating handle	External frontal External left side External right side

#### Ordering and shipping details

l11
00785901327417
1 Lb(US) (0.45 kg)
No
FR

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inhered as a substitute for and is not to be used for determining suitability or reliability of these products for specific user application for a product so that is the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative

### Offer Sustainability

cals including: S-	
cause cancer. For more informa-	
REACh Declaration	
Yes	
Compliant EPEU RoHS Declaration	
☑ China RoHS Declaration	
Product Environmental Profile	

## Contractual warranty

111	
Warranty	18 months

Product Life Status : Commercialised