Product data sheet Characteristics

LK4SU3N

Disconnect Switch, TeSys LK, nonfusible, 600A, 600 V, HP rated, 3 pole, rotary handle, up to 200kA SCCR

Product availability: Stock - Normally stocked in distribution facility

Price*: 2873.00 USD



Main

| TeSys | |
|-------------------------------|------------------------------------------------------------|
| TeSys LK | |
| Disconnect Switch | |
| Non-fusible disconnect switch | |
| Yes | |
| | TeSys LK Disconnect Switch Non-fusible disconnect switch |

Complementary

| Complementary | |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Poles description | 3P |
| Network type | AC DC |
| Network frequency | 50/60 Hz |
| [le] rated operational current | 200 A690 V AC AC-23A IEC 630 A400 V AC AC-22A IEC 630 A400 V AC AC-23A IEC 500 A690 V AC AC-22A IEC 600 A CSA 600 A UL |
| [Ue] rated operational voltage | 600 V AC 50/60 Hz |
| [Ui] rated insulation voltage | 1000 V |
| Control type | Rotary handle |
| Type of operating handle | External right side External frontal |
| Mounting support | Plate |
| [Uimp] rated impulse withstand voltage | 12 KV IEC |
| Rated power in W | 185 KW 690 V 355 KW 400 V 450 KW 500 V |
| Rated power in hp | 350 Hp 600 V 336 A AC 20 Hp 125 V 148 A DC 50 Hp 250 V 173 A DC 200 Hp 240 V 480 A AC 400 Hp 480 V 477 A AC |
| [lcw] rated short-time withstand current | 48 KA |

| Mechanical durability | 6000 Cycles | |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Electrical durability | 1000 Cycles | |
| Connections - terminals | Lugs-ring terminals 2 0.05 in² (34 mm²) bars 2 30 x 5 mm | |
| Height | 11.81 ln (300 mm) | |
| Width | 11.02 ln (280 mm) | |
| Depth | 5.51 ln (140 mm) | |
| Environment | | |
| Standards | CSA C22.2 No 4 IEC 60947-3 UL98 | |
| Product certifications | CSA UL CE | |
| Ordering and shipping details | | |
| Category | 22640 - IEC DISCONNECT-GS1,LK3 | |
| Discount Schedule | l11 | |
| GTIN | 00785901546870 | |
| Package weight(Lbs) | 18.72 Lb(US) (8.49 kg) | |
| Returnability | Yes | |
| Country of origin | FR | |
| Packing Units | | |
| Package 2 Weight | 93.61 Lb(US) (42.46 kg) | |
| 0.00 | | |
| Offer Sustainability | MADNING. This graduates a suppose of the description of the Co. | |
| California proposition 65 | WARNING: This product can expose you to chemicals including: S- tyrene, which is known to the State of California to cause cancer. For more informa- tion go to www.P65Warnings.ca.gov | |
| REACh Regulation | REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant E EU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| | Yes | |
| Mercury free | | |
| Mercury free RoHS exemption information | ☑ Yes | |

| Product Life Status : | Commercialised | |
|-----------------------|----------------|--|

18 months

Warranty