Product data sheet Characteristics

ZB5AV04

red pilot light head ø22 plain lens for ba9s bulb





Main

Range of product	Harmony XB5	
Product or component type	Head for pilot light	
Product compatibility	BA 9s	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Mounting diameter	22 Mm	
Head type	Standard	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Cap/operator or lens colour	Red	
Operator additional information	With plain lens	·

Complementary

CAD overall width	29 Mm	
CAD overall height	29 Mm	
CAD overall depth	31 Mm	
Net weight	0.018 Kg	
Station name	XALD 15 cut-outs XALK 25 cut-outs	
Electrical composition code	P3 in front mounting with BA 9s P4 in front mounting with BA 9s and transformer PF2 in front mounting with BA 9s	
Device presentation	Basic element	

Environment

Protective treatment	TH	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4070 °C	
Overvoltage category	Class II conforming to IEC 60536	
IP degree of protection	IP66 conforming to IEC 60529 IP67 conforming to IEC 60529 IP69 conforming to IEC 60529 IP69K conforming to ISO 20653	
NEMA degree of protection	NEMA 13 NEMA 4X	
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
IK degree of protection	IK05 conforming to IEC 50102	

Standards	EN/IEC 60947-5-1
	CSA C22.2 No 14
	EN/IEC 60947-5-5
	EN/IEC 60947-5-4
	JIS C8201-5-1
	EN/IEC 60947-1
	UL 508
	JIS C8201-1
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming-
	to IEC 60068-2-27
	50 gn (duration = 11 ms) for half sine wave acceleration conforming-
	to IEC 60068-2-27

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	15 G	
Package 1 Height	3.4 Cm	
Package 1 width	4.5 Cm	
Package 1 Length	5.4 Cm	
Package 2 Weight	75 G	
Package 3 Weight	5.006 Kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	[☑] End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised

