

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, B10, for single locking latch, height: 87.5 mm, without EVO screw connection

#### Your advantages

- Flexible cable outlet direction, lateral or straight
- Lower costs than metal version
- ☑ Labeling option using 9 x 20 mm marking label
- Low weight
- ☑ Lower risk of condensation
- If Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs
- Completely corrosion-resistant
- Malogen-free plastic
- Marking label can be attached



### Key Commercial Data

| Packing unit                         | 1 pc            |
|--------------------------------------|-----------------|
| GTIN                                 | 4 046356 776899 |
| GTIN                                 | 4046356776899   |
| Weight per Piece (excluding packing) | 100.000 g       |
| Custom tariff number                 | 85389099        |
| Country of origin                    | Poland          |

### Technical data

#### Dimensions



## Technical data

#### Dimensions

| Height | 87.5 mm |
|--------|---------|
| Width  | 44 mm   |
| Length | 73 mm   |

#### Ambient conditions

| Degree of protection (IP)       | IP66          |
|---------------------------------|---------------|
| Degree of protection (NEMA)     | 12 (UL 50e)   |
| Ambient temperature (operation) | -40 °C 125 °C |

#### General

| Note                                   | For contact inserts HC-B10, BB18, DD42, M, K8/24, HV03-I-PT, HC- 3-<br>EC   |
|--|---|
| Size                                   | B10   |
| Housing type                           | Sleeve housing  |
| Color                                  | black   |
| Locking type                           | for single locking latch  |
| No. of cable outlets                   | 1   |
| Cable outlet                           | straight  |
|  | lateral   |
| Screw connection                       | none  |
| Housing material                       | РА  |
| Seal material                          | NBR   |
| Flammability rating according to UL 94 | V0 (Housing)  |
| Connection                             | The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in 4 sizes. It enables the creation of a straight or lateral cable outlet. The EVO screw connection is mounted by hand or with the aid of a pipe wrench, for example. |


### **Environmental Product Compliance**

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

## Drawings



#### Dimensional drawing



Dimensional drawing

### Classifications

eCl@ss

| eCl@ss 10.0.1 | 27440202 |
|---------------|----------|
| eCl@ss 11.0   | 27440202 |
| eCl@ss 4.0    | 27140800 |
| eCl@ss 4.1    | 27140800 |
| eCl@ss 5.0    | 27143400 |
| eCl@ss 5.1    | 27261200 |
| eCl@ss 6.0    | 27261200 |
| eCl@ss 7.0    | 27440202 |
| eCl@ss 8.0    | 27440202 |
| eCl@ss 9.0    | 27440202 |

#### ETIM

| ETIM 3.0 | EC000437 |
|----------|----------|
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |
| ETIM 6.0 | EC000437 |
| ETIM 7.0 | EC000437 |

### UNSPSC

| UNSPSC 6.01   | 31261502 |
|---------------|----------|
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261501 |
| UNSPSC 18.0   | 31261501 |
| UNSPSC 19.0   | 31261501 |
| UNSPSC 20.0   | 31261501 |



## Classifications UNSPSC 31261501 UNSPSC 21.0 Approvals Approvals Approvals UL Recognized / cUL Recognized / EAC / DNV GL / cULus Recognized Ex Approvals Approval details http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E255026 **UL Recognized** 97 cUL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E255026 EHC RU C-EAC DE.AI30.B.01102 DNV GL TAE000037S https://approvalfinder.dnvgl.com/ DNV-GL cULus Recognized

#### Accessories

Accessories

Cable gland with bayonet locking



### Accessories

Cable gland - HC-B-G-M20-PLRBK - 1407669



EVO plastic cable gland with bayonet locking, for housing series B, size M20, cable diameter: 7 ... 13 mm

Cable gland - HC-B-G-M25-PLRBK - 1407670



EVO plastic cable gland with bayonet locking, for housing series B, size M25, cable diameter: 9 ... 17 mm

Cable gland - HC-B-G-M32-PLRBK - 1407671



EVO plastic cable gland with bayonet locking, for housing series B, size M32, cable diameter: 11 ... 21 mm

Cable gland - HC-B-G-M40-PLRBK - 1407672



EVO plastic cable gland with bayonet locking, for housing series B, size M40, cable diameter: 19 ... 28 mm

Corrugated pipe screw connection

Corrugated tube screw connection - HC-B-GCA-M20-PLRBK - 1412021



EVO corrugated pipe screw connection, size: M20, protection class: IP66, plastic



### Accessories

Corrugated tube screw connection - HC-B-GCA-M25-PLRBK - 1411973



EVO corrugated pipe screw connection, size: M25, protection class: IP66, plastic

Corrugated tube screw connection - HC-B-GCA-M32-PLRBK - 1412022



EVO corrugated pipe screw connection, size: M32, protection class: IP66, plastic

Corrugated tube screw connection - HC-B-GCA-M40-PLRBK - 1412023



EVO corrugated pipe screw connection, size: M40, protection class: IP66, plastic

Device marking

Snap-in markers - US-EMP (20X9) - 0829439



Snap-in markers, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped into marker carrier, lettering field size: 20 x 9 mm, Number of individual labels: 70

Protective cover

Protective covers - HC-B10-HCLWS-PLR-BK - 1414635



Protective cover B10, with single locking latch, protective cover material: PA, height: 21.6 mm, seal: yes, diameter of retaining cord eyelet: 30 mm



### Accessories

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com